



## XFT183


**ELECTRIC** 



| capacity   | 3 600x400      |
|------------|----------------|
| distance   | 75 mm          |
| frequency  | 50 / 60 Hz     |
| Voltage    | 230 V~ 1N      |
| power      | 3,3 kW         |
| Dimensions | 800x770x429 mm |
| weight     | 40 kg          |









| ■ :Standard □ :Optional - :Not available   | MATIC | DYNAMIC | CLASSIC | MANUAL HUM. |
|--|-------|---------|---------|-------------|
| BAKING MODES   |       |         |         |             |
| Convection baking 30 °C - 260 °C   | •     | •       | •       | •           |
| Mixed humidity and convection baking 90 °C - 260 °C  | •     | •       | -       | •           |
| AIR DISTRIBUTION IN THE BAKING CHAMBER   |       |         |         |             |
| AIR.Plus technology: fans with reversing gear on models 600x400  | •     | •       | •       | •           |
| AIR.Plus technology: fans with reversing gear on models 460x330  | •     | •       | •       | -           |
| CLIMA MANAGEMENT IN THE BAKING CHAMBER   |       |         |         |             |
| DRY.Plus technology: quick extraction of the humidity from the baking chamber                                  | •     | •       | •       | •           |
| STEAM.Plus technology: humidity injection that can be set from the control panel with 20% increment            | •     | •       | -       | -           |
| STEAM.Plus technology: manual humidity injection   | -     | -       | -       | •           |
| Pump that allows the oven to draw water from the tank (for models 460x330)                                     | •     | •       | -       | •           |
| Solenoid valve that allows the connection between oven and water directly (for models 600x400)                 | •     | •       | -       | •           |
| PANS   |       |         |         |             |
| Aluminium flat pans (for models 460x330)   | •     | •       | •       | •           |
| AUXILIARY FUNCTIONS  |       |         |         |             |
| 99 baking programs memory, each one made up of 3 baking steps + pre-heating                                    | •     | •       | •       | -           |
| Protek.SAFE™ technology: maximum thermal efficiency and working safety (cool door glass and external surfaces) |       | •       | •       | •           |
| Visualisation of the residual baking time  | •     | •       |         | •           |
| Continuous functioning «INF»   | •     | •       |         | •           |
| Visualisation of the set and real temperature values in the oven chamber                                       | •     | •       |         | -           |
| Temperature unit that can be set in °C or °F   | •     | •       | •       | -           |
| DOOR OPENING   |       |         |         |             |
| Manual door opening from top to bottom   | -     | •       | •       | •           |
| Flag opening door from right to left   | •     | -       | -       | -           |
| Automatic door opening at the end of the baking process  | •     | -       | -       | -           |
| TECHNICAL DETAILS  |       |         |         |             |
| Rounded stainless steel chamber for hygiene and easy of cleaning   | •     | •       | •       | •           |
| Oven chamber lighting with halogen lamp  | •     | •       | •       | •           |

| Light weight – heavy duty structure using innovative materials |   | • | • | • |
|--|---|---|---|---|
| Proximity door contact switch on models 600x400                |   | • | • | • |
| Proximity door contact switch on models 460x330                | • | • | • | - |
| Autodiagnosys system for problems or brake down                | • | • | • | - |
| Safety temperature switch                                      | • | • | • | • |